
OBERSOUND, CLASSIC COLLECTION

References with Oberflex finish

References from the Prestige d'Oberflex and Chic & Pop collections

References with unfinished wood veneer

References from Brut d'Ober and Bioply collections

Substrates

Particle board (standard, moisture-resistant or fire-resistant)

MDF (standard or fire-resistant)

Others : please consult us

Substrate thickness

Particle board : 10 mm . 12 mm . 16 mm . 19 mm . 22 mm .

MDF : 16 mm . 19 mm (others, consult us)

Dimensions

Unfinished edges :

Particle board and MDF : 3040 x 1230 mm ou 2500 x 1230 mm (except Textured Wood in Black and White Oak references : 3010 x 1210 mm ou 2500 x 1210 mm)

Precision-milled edges :

Particle board and MDF : 3030 x 1220 mm or 2490 x 1220 mm (except Textured Wood in Black and White Oak references : 3000 x 1200 mm or 2490 x 1200 mm)

On request : any dimension not exceeding 3030 x 1220 mm (except Textured Wood in Black and White Oak references : 3000 x 1200 mm)

Ceilings : 600 x 600 mm . 1200 x 600 mm

Others, consult us.

Counterbalancing

A/A - 2 visibles sides / same wood species

A/C - 1 visible side / 1 counterbalancing side (second grade Oberflex)

A/P - 1 visible side / 1 counterbalancing side (white decor)

Perforations

round . slotted . grooved / perforated

Edge treatment

Unfinished or veneered with the Oberflex edge banding (see page 96)

Edge machining

Rough-cut . calibrated . custom-treated : grooved, rebated, angle machining, bevelled machining

Others, please consult us.

Fire ratings

M2 / standard particle board and MDF

M1 / fire-resistant particle board and MDF

Euroclass B

Additional products

Black felt : On request, supply and installation of a black felt on the back of the panels.

Fixing profiles : see pages 139 and 140

THE RESISTANCE OF THE OBERFLEX FINISH



Abrasion
resistance



Impact
resistance



Scratch
resistance



Light
resistance



No attack by
common-type
products



Cigarette
burning
resistance



Can be
cleaned with
soapy water



Fire
resistance