



UNILIN Evola-Antivlam[®]

Melamine faced fire-retardant and non-structural chipboard for interior and furniture available in an extensive range of UNILIN Evola designs

Melamine faced fire-retardant and non-structural P2 chipboard. UNILIN Evola-Antivlam is suitable for dry conditions, service class 1, mainly used for interior and furniture. This fire-retardant product is B-s1,d0 certified. UNILIN Evola-Antivlam is made from 100% recovered wood: up to 90% post-consumer wood, supplemented by 10% pre-consumer wood from waste flows from the wood industry or thinned wood from sustainable forestry and verge management.

Applications

- Interior design
- Furniture production
- Vertical applications

Characteristics



P2



Melamine faced chipboard



Fire retardant (B-s1,d0)



100% recovered wood



UNILIN Evola-Antivlam[®]

Applications

UNILIN Evola-Antivlam is applied in different applications for interior and furniture design mainly where extra fire regulations are required.

Advantages

- In perfect colour match with HPL & edging tape for all UNILIN Evola stockrange decors
- Fire retardant
- Easy to clean
- Resistant to UV light
- Budget friendly
- Easy to process
- 100% recovered wood

Technical specifications

Performance characteristics	Unit	Ranges of nominal thickness (mm)		
	mm	>10-13	>13-20	>20-25
Bending strength EN 310	N/mm ²	11	11	10,5
Bending stiffness EN 310	N/mm ²	NPD	NPD	NPD
Internal bond EN 319	N/mm ²	0,40	0,35	0,30
Water vapour permeability	Wet %	16	15	15
	Dry %	50	50	50

Finish

This melamine faced board is possible to have in combination with a wide variety of designs.

The wood decors not only look incredibly lifelike, also the structures feel particularly authentic. Combined with plain colours, basis on international trends, the designs deliver unprecedented freedom in creativity for interior projects.

Available dimensions / thicknesses

All designs from UNILIN Evola collection are available on request in combination with Antivlam board.

Standard size is 2800x2070 and/or 3050x1250.

Thicknesses from service program (10,12,16,18 and 19mm) are ready to pick up within maximum 10 working days in size 2800x2070.

All info on dimensions and sizes is available in our pricelist.

Certificates

UNILIN Division Panels is actively committed to sustainable forest management. UNILIN Evola-Antivlam is available on demand in PEFC and/or FSC labelling.